

03.03 – NEUCEBEL – Exterior / Interior Acrylic Paint

DESCRIPTION:



Based on an acrylic dispersion of great quality, this paint offers a good resistance in the exterior being also a good solution for interior walls with regular cleanings. With resistance to mosses and algae development.

Provides a tinting of a wide range of colors in the BIG MIX system.

FEATURES:

- Easy application and good adhesion.
- Resistant to soap-and-water cleanup.
- Good lacquering and coverage.
- Good covering power.

SPECIFICATIONS:

- **Density** 1,500 ± 0,10 (p/ white color)
- **Viscosity**..... 85-115Ku (25°C)
- **Color**.....White, as in the catalog and others
- **Finishing**..... Matte
- **Dry-to-touch**..... ± 1 hour
- **Depth drying**..... ± 24 hours
- **Tenor in CIT/MIT**.....<15 ppm
- **VOC (volatile organic composites)** ^{a)} EU limit value for this product cat. (A/g) 30 g/l (2010). This product contains 20 g/l VOC maximum.
- **Indoor Air Quality Classification according to french regulation and the standard EN ISO 16000 ... A⁺** (LQAI.MC.29/18)

RECOMMENDED USE:

It is aimed at exterior and interior walls painting, having a good action on the most varied surfaces, such as: sand-finish or flat plaster, concrete, brick, stucco walls, etc, allowing finishes in a wide range of matte colors shades.

SURFACE PREPARATION:

The new plaster has to be clean, dry, hard, free of any dirt, dust and alkaline efflorescence or “mosses”, before to start the application. In the case of repainting, a good brushing of the walls is advised, in order to eliminate old painting remains, or to exfoliate. On exterior walls, this operation is facilitated with the use of pressurized water-jet cleaning gun.

SURFACE INSULATION:

A careful choice of the 1st coat (insulation) helps to obtain a better finish and to solve certain existing problems in the painting surface. We recommend as special insulations:

- One coat of “PLIONEUCE PRIMER” – No dilution.
- One coat of “HYDRONEUCE PRIMER” ” – No dilution.
- One coat of “AQUANEUCE – White Water Based Acrylic Primer” – No dilution.

- One coat of “MARSOL – High Filling Acrylic Primer” – Diluted at 10% with water.
- One coat of “MULTINEUCE – Water Based Acrylic Multi-Use Primer” – No dilution.

APPLICATION: Before to use mix energetically the product.
The application is made with a paint-brush, a roller or a spray-gun in 2 to 3 coats properly diluted and in a period of 12 to 24 hours.

DILUTION: With water in the approximate following proportions:

1st Coat.....10%
Others.....5% to 10%

COVERAGE: Variable according to the support’s absorption, and the application conditions.
On average and per coat 11 to 15 m² / liter.

CLEAN-UP: With water right after the application

WARNING: This product is not irritant nor presents any risks of sensitization in a contact with skin. In spite of presenting no risks for health, it is advised to keep out of reach of children. For further information, the reading of our product **Safety Data Sheet** is essential.

RECOMMENDATIONS: Do not use on hot surfaces due to sun exposure. Application temperature is between 5°C and 35°C, relative humidity inferior to 80%, the surface temperature above the dew point between 2 and 3°C.

STORAGE AND PACKAGING: Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 2 years after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 1lt, 5lt and 15 liters.

Note a) The value of the VOC previously mentioned concerns ready-to-use products, according to the technical specifications that we recommend. We do not take any responsibility for other mixtures made to the product. We draw special attention to all our agents for the responsibility that they take by not respecting what the Directive 2004/42/CE establishes.