

W16 – PAVINEUCE SLURRY- Colored Coating for floors protection

DESCRIPTION:



PAVINEUCE SLURRY is a water-based coating of acrylic root specially developed for the protection and marking of floors: sportive, bicycle paths, playgrounds, etc. Composed of selected inert of controlled granulometry and pigments of high resistance and solidity to solar rays.

FEATURES:

- Easy to apply and good adhesion
- Good resistance to bad weather.
- Resistant to oils.
- Good abrasion resistance.
- Environment friendly, doesn't contain solvents.

SPECIFICATIONS:

- **Density**.....1,670 ± 0,10
- **Viscosity**.....10500±1050 cp SP7 60rpm (25°C)
- **Color**.....Red, green and others upon request
- **Superficial drying**.....2 to 4 hours
- **Depth drying**.....± 24 hours.
- **Recoat**.....12 to 24 hours
- **VOC (volatile organic compound)**....^{a)} EU limit value set for this product cat. (A/i) 140 g/l (2010). This product contains a maximum of 1.6 g/l VOC.

RECOMMENDED USE:

PAVINEUCE SLURRY is generally used for the finish of pavements of concrete, cement or putty mixtures, improving the esthetic aspect:

- Bicycle paths and pedestrian walks
- Sportive track and playtime areas
- Kerbs, separators and roundabouts
- Playgrounds
- Pavements of garages and parking, where the traffic of tires is little and moderated
- Environmental-friendly routes; tourist routes, pilgrimages routes, etc

SURFACE PREPARATION:

The support on which will be applied the coating, has to be clean, free of dust, grease and humidity.

- APPLICATION:** To homogenize well the product before to apply, since that, with the product storage time, the inerts tend to deposit.
To spread the product in uniform layers using a squeegee with a soft blade, a roller, spray-gun or any appropriated tool. Then, for a better uniformity and equalizing of the layer, a short nap roller can be used.
To let the layer properly dry, 12 to 24 hours, before to apply the next one, depending on the humidity degree and the environment temperature.
The application is made with 1 to 2 coats of PAVINEUCE SLURRY, depending on the opacity of the chosen color and the surface absorption / compaction.
- DILUTION:** With water, only on the 1st coat up to a maximum of 10%, when it is a very compact and/or little absorbent surface.
- COVERAGE:** On average and per coat : 0.5-1 Kg/m², depending on the application method, the roughness and the base absorption.
It can reach a coverage of 1-2 Kg/m², per coat, in very absorbent and rough surfaces.
- CLEAN-UP:** With water, right after the application.
- WARNING:** This product is not irritant nor presents any risks of sensitization in a contact with the skin. In spite of presenting no risks for health, it is advised to keep out of reach of children. For further information, the reading of our product **Safety Data Sheet** is essential
- RECOMMENDATIONS:** We advise to apply and cure the product with temperatures superior to 8°C and inferior to 35°C.
The application must only be made with a dry weather, but not in very hot days and with a moderate exposition to the U.V. rays. In the hottest months, the product should be preferably applied early in the morning.
To make sure that, in the same area, to only apply material of the same manufacturing order (MO). Different MO can have little color differences.
- STORAGE AND PACKAGING:** Packages should be kept properly closed, in good environmental conditions of temperature and humidity, and spend the product on the chronological order of supply.
Use it, with preference, up to 1 year after its manufactured date, but it can also be used after this date, as long as a good homogenization of the product can be verified.
It is supplied in packages of 25 Kg.